

Manual Call Point FD7150



The manual call point FD7150 is designed for indoor installation as a component of an Addressable Fire Alarm System IFS7000 series. The unit is compatible with the requirements of the European Standard EN54-11:2001/A1:2005, EN54-17:2005/AC:2007.

The FD7150 manual call point has a built-in short circuit isolator for the signal loop. The communication between the addressable manual call point and the Panel is based on a private UniTalk protocol.

Technical data

Supply voltage:
– (10-30) VDC

Degree of protection:
– IP 40

Current in quiescent state:
– < 390 μ A

Current in alarm state:
– (3 \pm 1) mA

Electrical installation:
Through terminal for connecting wires with cross-section (0,5-1,5) mm²

Operational temperature range: -10°C to +55°C

Relative humidity resistance: (93 \pm 3)% at 40°C

Dimensions: 98 x 96 x 51 mm

Weight of the manual call point: 0.150 kg

The LED indicator provides the following status information:

– **Duty mode:**
the LED flashes shortly on 16s period

– **Alarm condition:**
the LED flashes with continuous light

– **Activated short circuit isolator:**
the LED flashes shortly on 1s period



Istanbul Deri organiz Sanayi Bolgesi, Sama Caddesi

NO:8M1-5 Ozel Parsel, Tuzla/Istanbul

0216 394 01 55-0216 394 01 56 0216 394 25 73

0216 394 05 30-0216 394 01 98 0216 394 01 64